

Performance Evaluation:

General full factorial design with k factors

Hongwei Zhang

<http://www.cs.wayne.edu/~hzhang>



Work expands to fill the time available for its completion.

--- C. Northcote Parkinson

Acknowledgement: this lecture is partially based on the slides of Dr. Raj Jain.

Outline

- Model
- Analysis of a General Design
- Informal Methods
 - Observation Method, Ranking Method
 - Range Method

Outline

- Model
- Analysis of a General Design
- Informal Methods
 - Observation Method, Ranking Method
 - Range Method

Model

□ k factors $\Rightarrow 2^k - 1$ effects

k main effects

$\binom{k}{2}$ two factor interactions,

$\binom{k}{3}$ three factor interactions, and so on.

Example: 3 factors A, B, C:

$$y_{ijkl} = \mu + \alpha_i + \beta_j + \xi_k + \gamma_{ABij} + \gamma_{ACik} + \gamma_{BCjk} + \gamma_{ABCijk} + e_{ijkl}$$

$$i = 1, \dots, a; \quad j = 1, \dots, b; \quad k = 1, \dots, c;$$

$$l = 1, \dots, r;$$

Model (contd.)

y_{ijkl}	=	Response in the l th replication with factors A, B, and C at levels i , j , and k , respectively.
μ	=	Mean response
α_i	=	Effect of factor A at level i
β_j	=	Effect of factor B at level j
ξ_k	=	Effect of factor C at level k
γ_{ABij}	=	Interaction between A and B at levels i and j .
γ_{ABCijk}	=	Interaction between A, B, C at levels i , j , and k .
		and so on

Outline

- Model
- Analysis of a General Design
- Informal Methods
 - Observation Method, Ranking Method
 - Range Method

Analysis of a general design

- Similar to that with two factors

$$\mu = \bar{y}_{....}$$

$$\alpha_i = \bar{y}_{i...} - \bar{y}_{....}$$

- The sums of squares, degrees of freedom, and F-test also extend as expected.

Case study

Factors and Levels for Page Swap Study

Symbol	Factor	Levels		
		1	2	3
A	Page Replacement Algorithm	LRUV	FIFO	RAND
D	Deck Arrangement	GROUP	FREQY	ALPHA
P	Problem Program	Small	Medium	Large
M	Memory Pages	24P	20P	16P

- Total 81 experiments.

Case study (contd.)

□ Total Number of Page Swaps

Algor- ithm	Prog- ram	GROUP			FREQU			ALPHA		
		24P	20P	16P	24P	20P	16P	24P	20P	16P
LRUV	Small	32	48	538	52	244	998	59	536	1348
	Medium	53	81	1901	112	776	3621	121	1879	4639
	Large	142	197	5689	262	2625	10012	980	5698	12880
FIFO	Small	49	67	789	79	390	1373	85	814	1693
	Medium	100	134	3152	164	1255	4912	206	3394	5838
	Large	233	350	9100	458	3688	13531	1633	10022	17117
RAND	Small	62	100	1103	111	480	1782	111	839	2190
	Medium	96	245	2807	237	1502	6007	286	3092	7654
	Large	265	2012	12429	517	4870	18602	1728	8834	23134

□ $y_{\max}/y_{\min} = 23134/32 = 723 \Rightarrow \log$ transformation

Large



Case study (contd.)

□ Transformed Data For the Paging Study

Algor- ithm	Prog- ram	GROUP			FREQU			ALPHA		
		24P	20P	16P	24P	20P	16P	24P	20P	16P
LRUV	Small	1.51	1.68	2.73	1.72	2.39	3.00	1.77	2.73	3.13
	Medium	1.72	1.91	3.28	2.05	2.89	3.56	2.08	3.27	3.67
	Large	2.15	2.29	3.76	2.42	3.42	4.00	2.99	3.76	4.11
FIFO	Small	1.69	1.83	2.90	1.90	2.59	3.14	1.93	2.91	3.23
	Medium	2.00	2.13	3.50	2.21	3.10	3.69	2.31	3.53	3.77
	Large	2.37	2.54	3.96	2.66	3.57	4.13	3.21	4.00	4.23
RAND	Small	1.79	2.00	3.04	2.05	2.68	3.25	2.05	2.92	3.34
	Medium	1.98	2.39	3.58	2.37	3.18	3.78	2.46	3.49	3.88
	Large	2.42	2.30	4.09	2.71	3.69	4.27	3.24	3.95	4.36

Case study (contd.)

□ Effects: $\alpha_1 = y_{1\dots} - y_{\dots} = 2.74 - 2.90 = -0.16$

Main Effects			
	Level		
Factor	1	2	3
A	-0.16	0.02	0.14
D	-0.36	0.07	0.29
P	-0.47	-0.02	0.49
M	-0.69	-0.01	0.70

Also

- Six two-factor interactions,
- Four three-factor interactions, and
- One four-factor interaction.

Case study (contd.) – ANOVA table

Component	Sum of Squares	%Variation	DF	Mean Square
y	730.01		81	
\bar{y}	681.21		1	
$y-\bar{y}$...	48.80	100%	80	
Main Effects	45.80	93.85%	8	5.7
A	1.30		2	
D	6.10		2	
P	12.30		2	
M	26.20		2	
First-order Interactions	2.40	4.91%	24	0.1
AD	0.07		4	
AP	0.02		4	
AM	0.03		4	
DP	0.15		4	
DM	<u>1.96</u>		4	
PM	0.14		4	
Second-order Interactions	0.48	0.98%	32	0.015
ADP	0.05		8	
ADM	0.13		8	
APM	0.04		8	
DPM	0.26		8	
Third-order Interaction (ADPM)	0.07	0.14%	16	0.004

Case study (contd.)

- Most interactions except DM are small => simplified model

$$y_{ijkl} = \mu + \alpha_i + \beta_j + \gamma_k + \delta_l + \xi_{jl}$$


Where,

μ	=	grand mean
α_i	=	Effect of A
β_j	=	Effect of D
γ_k	=	Effect of P
δ_l	=	Effect of M
ξ_{jl}	=	Interaction between D and M.

Case study (contd.) – errors

Algor- ithm	Prog- ram	GROUP			FREQUENCY			ALPHA		
		24P	20P	16P	24P	20P	16P	24P	20P	16P
LRUV	Small	0.18	0.08	-0.07	0.11	-0.04	-0.02	-0.05	-0.04	0.01
	Medium	-0.05	-0.13	0.04	0.01	0.02	0.10	-0.18	0.07	0.11
	Large	-0.13	-0.26	0.01	-0.14	0.04	0.03	0.22	0.04	0.04
FIFO	Small	0.17	0.04	0.09	0.11	-0.02	-0.07	-0.08	-0.04	-0.08
	Medium	0.05	-0.10	0.07	-0.02	0.04	0.05	-0.13	0.14	0.02
	Large	-0.10	-0.20	0.02	-0.00	0.00	-0.03	0.25	0.09	-0.02
RAND	Small	0.16	0.09	-0.06	0.14	-0.05	-0.07	-0.08	-0.08	-0.08
	Medium	-0.10	0.04	0.04	-0.02	0.00	0.01	-0.11	-0.02	-0.02
	Large	-0.17	0.44	0.04	-0.15	0.00	-0.01	0.16	-0.08	-0.01

Case study (contd.) – visual test



Almost a straight line.

Outlier was verified.

Outline

- Model
- Analysis of a General Design
- **Informal Methods**
 - Observation Method, Ranking Method *To find the best combination of factor levels*
 - Range Method *To find out the importance of a factor*

Observation method

- Applied when
 - the response variable is a HB (higher is better) or LB (lower is better) metric, and
 - the goal is to find the best factor-level-combination that produces the best response
- Method: simply look at the response column, and the experiment corresponding to the highest/lowest response gives the desired combination

Example: scheduler design

- Three Classes of Jobs:
 - Word processing
 - Interactive data processing
 - Background data processing
- Five Factors 2^{5-1} (fractional factorial) design

Example (contd.)

- Measured throughput

No.	A	B	C	D	E	T_W	T_I	T_B
1	-1	-1	-1	-1	1	15.0	25.0	15.2
2	1	-1	-1	-1	-1	11.0	41.0	3.0
3	-1	1	-1	-1	-1	25.0	36.0	21.0
4	1	1	-1	-1	1	10.0	15.7	8.6
5	-1	-1	1	-1	-1	14.0	63.9	7.5
6	1	-1	1	-1	1	10.0	13.2	7.5
7	-1	1	1	-1	1	28.0	36.3	20.2
8	1	1	1	-1	-1	11.0	23.0	3.0
9	-1	-1	-1	1	-1	14.0	66.1	6.4
10	1	-1	-1	1	1	10.0	9.1	8.4
11	-1	1	-1	1	1	27.0	34.6	15.7
12	1	1	-1	1	-1	11.0	23.0	3.0
13	-1	-1	1	1	1	14.0	26.0	12.0
14	1	-1	1	1	-1	11.0	38.0	2.0
15	-1	1	1	1	-1	25.0	35.0	17.2
16	1	1	1	1	1	11.0	22.0	2.0

Example (contd.)

- Conclusion:

To get high throughput for word processing jobs,:

1. There should not be any preemption ($A=-1$)
2. The time slice should be large ($B=1$)
3. The fairness should be on ($E=1$)
4. The settings for queue assignment and re-queueing do not matter.

Ranking method

- First, sort experiments according to response
- Then, observe the factor columns to find levels that consistently produce good/bad results
- Similar to observation method, but usually gives more information

Example: for word processing

No.	A	B	C	D	E	T_W	T_I	T_B
7	-1	1	1	-1	1	28.0	36.3	20.2
11	-1	1	-1	1	1	27.0	34.6	15.7
15	-1	1	1	1	-1	25.0	35.0	17.2
3	-1	1	-1	-1	-1	25.0	36.0	21.0
1	-1	-1	-1	-1	1	15.0	25.0	15.2
5	-1	-1	1	-1	-1	14.0	63.9	7.5
9	-1	-1	-1	1	-1	14.0	66.1	6.4
13	-1	-1	1	1	1	14.0	26.0	12.0
2	1	-1	-1	-1	-1	11.0	41.0	3.0
8	1	1	1	-1	-1	11.0	23.0	3.0
12	1	1	-1	1	-1	11.0	23.0	3.0
14	1	-1	1	1	-1	11.0	38.0	2.0
16	1	1	1	1	1	11.0	22.0	2.0
6	1	-1	1	-1	1	10.0	13.2	7.5
4	1	1	-1	-1	1	10.0	15.7	8.6
10	1	-1	-1	1	1	10.0	9.1	8.4

Example: conclusion

1. $A=-1$ (no preemption) is good for word processing jobs and also that $A=1$ is bad.
2. $B=1$ (large time slice) is good for such jobs. No strong negative comment can be made about $B=-1$.
3. Given a choice C should be chosen at 1, that is, there should be two queues.
4. The effect of E is not clear.
5. If top rows chosen, then $E=1$ is a good choice.

Range method

- ❑ Range = Maximum-Minimum
- ❑ Factors with large range are important.

Factor	Level			Range of of Averages
	1	2	3	
Replacement Algorithm	2056	2986	3781	1725
Deck Arrangement	1584	2913	4326	2742
Problem Program	592	2047	6185	5593
Memory Size	305	2006	6512	6207

Memory size is the most influential factor.

Problem program, deck arrangement, and replacement algorithm are next in order.

Summary

- Model
- Analysis of a General Design
- Informal Methods
 - Observation Method, Ranking Method
 - Range Method

Homework #3

(100 points)

Analyze the following results using observation and ranking methods.

No.	A	B	C	D	E	<i>T</i>
1	-1	-1	-1	-1	1	13.2
2	1	-1	-1	-1	-1	4.0
3	-1	1	-1	-1	-1	22.0
4	1	1	-1	-1	1	9.6
5	-1	-1	1	-1	-1	6.5
6	1	-1	1	-1	1	8.5
7	-1	1	1	-1	1	21.2
8	1	1	1	-1	-1	2.0
9	-1	-1	-1	1	-1	7.4
10	1	-1	-1	1	1	7.4
11	-1	1	-1	1	1	14.7
12	1	1	-1	1	-1	4.0
13	-1	-1	1	1	1	13.0
14	1	-1	1	1	-1	3.0
15	-1	1	1	1	-1	18.2
16	1	1	1	1	1	3.0